


■ 快插接头（整体高温式） P08-C405



[单位: mm]

型号选择 型号	R(PT)	适用软管 外径 D	P	C	L	L1	H	温度		
P08-C40501-4	1/8	4	9.9	14.5	20.6	8	10	100℃		
P08-C40501-6	1/8	6	11.8	16.6	22.2	8	12	100℃		
P08-C40501-8	1/8	8	13.8	17.7	27.4	8	14	100℃		
P08-C40501-10	1/8	10	16.8	20.0	30.1	8	17	100℃		
P08-C40502-4	1/4	4	9.9	14.5	23.6	11	14	100℃		
P08-C40502-6	1/4	6	11.8	16.6	26.2	11	14	100℃		
P08-C40502-8	1/4	8	13.8	17.7	26.1	11	14	100℃		
P08-C40502-10	1/4	10	16.8	20.0	30.1	11	17	100℃		
P08-C40502-12	1/4	12	19.8	22.6	35.2	11	21	100℃		
P08-C40503-6	3/8	6	11.8	16.6	26.2	12	17	100℃		
P08-C40503-8	3/8	8	13.8	17.7	26.4	12	17	100℃		
P08-C40503-10	3/8	10	16.8	20.0	28.6	12	17	100℃		
P08-C40503-12	3/8	12	19.8	22.6	31.2	12	21	100℃		
P08-C40504-10	1/2	10	16.8	20.0	32.6	15	22	100℃		
P08-C40504-12	1/2	12	19.8	22.6	33.2	15	22	100℃		
P08-C40501-4-F	1/8	4	9.9	14.5	20.6	8	10	120℃		
P08-C40501-6-F	1/8	6	11.8	16.6	22.2	8	12	120℃		
P08-C40501-8-F	1/8	8	13.8	17.7	27.4	8	14	120℃		
P08-C40501-10-F	1/8	10	16.8	20.0	30.1	8	17	120℃		
P08-C40502-4-F	1/4	4	9.9	14.5	23.6	11	14	120℃		
P08-C40502-6-F	1/4	6	11.8	16.6	26.2	11	14	120℃		
P08-C40502-8-F	1/4	8	13.8	17.7	26.1	11	14	120℃		
P08-C40502-10-F	1/4	10	16.8	20.0	30.1	11	17	120℃		
P08-C40502-12-F	1/4	12	19.8	22.6	35.2	11	21	120℃		
P08-C40503-6-F	3/8	6	11.8	16.6	26.2	12	17	120℃		
P08-C40503-8-F	3/8	8	13.8	17.7	26.4	12	17	120℃		
P08-C40503-10-F	3/8	10	16.8	20.0	28.6	12	17	120℃		
P08-C40503-12-F	3/8	12	19.8	22.6	31.2	12	21	120℃		
P08-C40504-10-F	1/2	10	16.8	20.0	32.6	15	22	120℃		
P08-C40504-12-F	1/2	12	19.8	22.6	33.2	15	22	120℃		